

Design Considerations That Help Avoid Electrical Disasters

David Brender, P.E.

Copper Development Association Inc.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Agenda

1. National Electrical Code minimum requirements
2. Considerations for sensitive equipment
3. Many case histories we can learn from



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What is Poor Power Quality


- Poor power quality...

is evidenced by characteristics of the incoming power to a device that deviate from the customary “pure” 60 Hz sine wave, and that can affect reliable and safe operation of the sensitive equipment




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What the Equipment Wants



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What the Equipment Sometimes Gets



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Overview of This Presentation

Elements of building infrastructure that can alleviate or cure power quality problems before they affect operations:

Grounding

Bonding

Circuiting

Lightning



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Equipment More Sensitive


- Micro circuits are getting faster (radio frequency range)
- Microprocessors more ubiquitous
- Circuits are getting smaller
- Operating voltages are lower



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Old vs. New

What used to be acceptable service characteristics are no longer sufficient



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The Real Cost

The real cost of poor power quality is in lost productivity (downtime).


- Estimated at \$15-30 billion per year plus in US
- Average cost of a data center outage \$740,357 in 2016
- Exceeds \$1 million/yr. at some buildings

- E Source and Penton



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Is The Computer a Problem? or is it the way it's wired?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Fire Alarm, Elevator and Parking Lot Lights

PANELBOARD/PANNEAU/TABLERO

V. DATE:

CIR	SOURCE LOAD / CHARGE / CARGA	CIR	LOAD / CHARGE / CARGA
1	Elevator main	2	Lobby AHU
3	disconnect	4	
5	Hyd. motor	6	
7	Lobby A/C	8	Surge
9	condenser unit	10	Protection
11	out Back	12	unit
13	Parking lot	14	Hot water
15	Light poles	16	Heater
17	Parking lot	18	space
19	Light poles	20	South Stair way LTS
21	outside front GFI	22	space
23	N+S GFI	24	North Stairway LTS + Emergency LTS
25	GFI under	26	Elevator Cab LTS
27	PHOTO cell	28	Fresh Air make up Fan
29	Entry Lobby GFI	30	Time clock
31	Fire Alarm Booster Pnl.	32	Elevator Pit is GFI
33	Fire Alarm Pnl.	34	Elevator Pit is LTS
35		35	



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
 SEPTEMBER 24-28 | LAS VEGAS, NV

Problems Are Mainly Internal

Most power quality problems are related to grounding and neutral size issues

Over 80% are internally caused

source: EPRI



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


NEC Is Bare Minimum Needed for Safety

Good starting point, BUT..

NEC is Not a PQ Code

NEC is Not a lightning Code

NEC is Not a good grounding Code



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Erratic Operation or Downtime

Power Quality issues can lead to erratic operation of sensitive electronic equipment (data errors, lockup, false images in medical diagnostics, downtime, etc.)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Cable Failures


**Overheating of phase conductors or neutrals,
nuisance tripping**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Motor Failures


Premature burnout of motor windings



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Effects of Poor Power Quality

Failure of electronic components



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Two Types of “Grounding”

- **System Grounding**
- **Equipment grounding (bonding)**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

“Grounding”

Oddly enough, “ground” is not defined in the NEC. **Grounded (Grounding)**. Connected (connecting) to ground or to a conductive body that extends the ground connection.

The ground path can carry current in the event of a fault.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

System or Exterior Grounding

- Needed for:
- Establishing a voltage reference
- Discharge high transient voltages (esp. lightning)
- Static Discharge
- Personnel Safety



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

“Bonding”

The intentional connection of normally non-current carrying parts of equipment together

The two terms are frequently used interchangeably




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Exterior Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Isokeraunic Map



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

NEC is NOT Sufficient

- **250.53 (A)(1)** If practicable, rod, pipe, and plate electrodes shall be embedded below permanent moisture level.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

NEC “Alludes” to 25 Ohms

Water Pipe and 2 ground rods, even if result exceeds 25 ohms.

- **250.53 (A)(2)** A single rod, pipe, or plate electrode shall be supplemented...



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

NEC “Alludes” to 25 Ohms

BUT

exception:

Exception: If a single rod, pipe, or plate grounding electrode has a resistance to earth of 25 ohms or less, the supplemental electrode shall not be required.

There are no testing parameters


Thus, if two rods are installed, you’re done!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

NEC Allows 6 Ft. Spacing


- **250.53 (A)(3) Supplemental Electrode.** If multiple rod, pipe, or plate electrodes are installed to meet the requirements of this section, they shall not be less than 1.8 m (6 ft.) apart.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

NEC Allows 30 Inch Depth

- **250.53 (F) Ground Ring.** The ground ring shall be buried at a depth below the earth's surface of not less than 750 mm (30 in.).



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Better Standard: IEEE Emerald Book

- ANSI/IEEE 1100

Recommended practices are needed for power quality.

800-678-IEEE



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

System Grounding

Desired Grounding Resistance:


- 5 ohms or less desired for power quality
- Many mfgs. specify under 2 ohms
- IEEE recommends 1-5 ohms (Green Book)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Concentric Shells of Earth Surround Rod

Varies with
rod length &
soil conditions



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Current=Voltage/Resistance



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

2X Rod Length (average) Dependent on Soil Resistivity





FIGURE 4-5 GROUNDING ELECTRODE SPHERE OF INFLUENCE



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Overlapping Spheres of Influence

Lowering Ground Resistance



Concentric Shell
Overlap Decreases
Efficiency of
Ground Rod
Resistance

39



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Poor Example of Ground Rod Spacing



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Ground Rod is Embedded in Conductive Concrete

and takes advantage of the fact 50% of the earth resistance is within 6" of the rod. (credit to gpr-expert.com)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Conductive Cement Effectively Enlarges the Contact with the Earth of the Wire.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Case History

Orange County, FL 911
13 transmitter sites



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Orange County, FL 911

**Headquarters
Apopka, FL**



Source: Power & System Innovations,
Inc., Orlando



**2017 BICSI *Fall*
CONFERENCE & EXHIBITION**
SEPTEMBER 24-28 | LAS VEGAS, NV

Headquarters Tower- Apopka, FL

280 foot tower

3 sets of 5 guys



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Equipment Damages

**\$100 K/yr. damage at
Apopka alone
Not including downtime**



**2017 BICSI *Fall*
CONFERENCE & EXHIBITION**
SEPTEMBER 24-28 | LAS VEGAS, NV

Internal Arcing



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Staff Knew They Needed Help

Staff was not expert in power quality, called in knowledgeable professional



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


3 Independent Grounds



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Refitted Site

Everything bonded together



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Ungrounded Equipment Cabinets



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Equipment Incorrectly Bonded

How Many Conductors Can You Get On One Split-bolt?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Outside Bulkhead

**Only ONE Cu strip
connected to electrode**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Facility Ground at Apopka

Main electrode was all-thread rod



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Original Ground Resistance

Measured 550 ohms



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Apopka Tower Grounding

**Retrofits:
Deep (60 ft.)
electrode
supplements tower**



**2017 BICSI *Fall*
CONFERENCE & EXHIBITION**
SEPTEMBER 24-28 | LAS VEGAS, NV

New Coax Grounding On Tower


for coax grounds then 4/0 to electrode



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Outside Bulkhead


strip bonded together and to ring with 4/0



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Bond Equipment Properly

Note double nuts and lockwasher



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Halo Rings

All equipment bonds brought to buses
Buses tied to halo rings



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Sweeping Curves



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Proper Coax Shield Grounding

- Andrews Cuffs



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Reedy Creek

**Remote repeater
near Disney World**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Reedy Creek


More real estate to work with



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Reedy Creek

Grounding layout: double rings plus deep electrodes



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

New Resistance 3.5Ω


< 5 ohms
independently



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Sweeping Turns


Note wide, large diameter turns



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Replaced Connections


How many wires can you fit in a split-bolt?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Ungrounded Equipment at Apopka


And this



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning Means Vibration

Lock washer, double nuts



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SPD's on Three Levels

SPD's on
main service
entrance



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Since Retrofit

- Thousands of events recorded
- One strike witnessed
- NO Downtime! No equipment damage.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Major Lessons

3 different contractors

- **electrical**
- **radio room**
- **tower**

**No one party had
responsibility**



**2017 BICSI *Fall*
CONFERENCE & EXHIBITION**
SEPTEMBER 24-28 | LAS VEGAS, NV

Power Quality is Cost-effective

OC 911:

<\$500,000 cured \$1 million damages

6-mos. to 1 year paybacks common



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Angel Fire Ski Resort



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Angel Fire Ski Resort

- 2001 Spring Break, lightning caused shutdown
- People stranded on lift
- Loss over \$2 M revenue



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Base Station

Base control house
Similar at top
Computer controlled



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Only Ground Between Towers



Grounding for communications cable



Terminus of messenger wire (only grounding between towers)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

System Was Not Integrated



- Ground *system*
- Rod at each tower
- 2 miles of 2/0, each tower connected
- Rings at top and bottom stations
- No outages since!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Exothermic Welding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lower Base Station


Soaking bentonite with
water



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Angel Fire Result

upper
control
house



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KKIT - FM



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Connection to Electrode



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Connection to Water Service



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Multi Building Campus Examples



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Verestar

Largest satellite facility in North America



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Verestar Control Room

6 buildings

Over 100 acres



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Dishes Are Remote

42 satellite dishes

3.5 m to 30 m




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Basic Grounding Layout

4/0 ring ground around each building (6)

750 kcmil spine

4/0 around each dish
(typ of 42)
2 Ohm standard



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

M.I.T. Case Study

Current Interior Design Standards:


Separate computer feeders, panels, and branch circuits

4 outlets per 20 amp. Branch circuit



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Separate Systems



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

M.I.T. Design Standards

Current Design Standards:


- 10 ohms or less grounding resistance
- Double (and sometimes triple) neutrals
- K-rated transformers
- Always a separate grounding conductor
- Always copper




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

M.I.T. Basic Grounding Layout

- 500 kcmil ring ground around each building



- 1000 kcmil spine



- Triangulated
- 20 ft. rods at all corners



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Limitations of Ufer Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KPTH & KMEG-TV



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


What Can Happen to a Ufer Ground?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KPTH & KMEG-TV


- 250 kcmil ring around tower
- 80 ft. deep earth electrodes
- Bonded to ice bridge
- Bonded to transmitter



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KPTH & KMEG-TV

- Site plan



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

High Water Table Does Not Mean Low R


KROA-FM, Donephin, NE

- 5 ft. water table, near Platte River
- **Water was “too” clean**
- Tower hit by lightning
- Went off air, equipment damaged / destroyed



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Hose Clamps on Plumbing Tube



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Tower Ground Connection



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KROA Result of Corrections

- Lightning vulnerability greatly reduced
- Hum on signal disappeared
- Able to rent out to a second station



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

KROA Lessons

- Pure water is not conductive
- Use only listed connectors
- Use only proper connections, listed proper components
- Pay attention to corrosion



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

“Clean” Grounds



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The Earth Cannot Be Used as a Conductor

Earth is never a satisfactory conductor

NEC, Art. 100:

Effective Ground-Fault Current Path. An **intentionally constructed, low-impedance electrically conductive** path designed and intended to carry current under ground-fault conditions from the point of a ground fault on a wiring system to the electrical supply source and that facilitates the operation of the overcurrent protective device or ground-fault detectors.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Case Study: “Clean Grounds”

McAfee Tool and Die



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

This is a High-Tech Environment




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Every CNC Machine is Computer-driven




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Comm Cable is Unintentional Antenna




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

So-called “Clean Grounds”




“Supplemental”
electrodes abandoned



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

McAfee Layout

Earth as a conductor




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Earth is Not Permitted as a Current Path

**No separate grounds allowed
only one grounding system**

- **250.54** ...the earth shall not be used as an effective ground-fault current path...



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What is an IG?

So if “supplemental” grounds are a no-no, what is an isolated (“insulated”) ground?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Insulated Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Insulated Grounding (IG)


Good idea to install in new circuits

Gives flexibility to use or not




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

This is NOT IG




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Isolated (Insulated) Grounding




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

IG Circuit with Transformer



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Not Connected to Cabinet




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Receptacles

IG or SG?



IG





Either receptacle
may be any
color under the
most recent
NEC editions.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Receptacles


Do you see the difference?




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Receptacles

IG or SG?




An orange color delta




is required to be
embossed on the face

IG



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Why use IG?



The use of solidly grounded branch circuits sometimes results in too much “noise” on the branch circuit for reliable operation of the electronic loads.

IG is not subject to induced energy of nearby lightning, thus smaller SPD's



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Let's Take a Break



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

When You Are Involved

- When your equipment is involved, you should be the expert when you walk on site.
- You are responsible to be sure all is right if not, you fix it.
- If you don't have the expertise to "fix", get an expert involved. The key dazzle with brilliance not baffle with BS.
- Learn how to recognize issues that will impact the proper installation of your equipment and its sustainability.
- Inform your customer of the conditions that can impact your installed equipment.
- Some will "ignore" and hope issues go away. Put it in writing, inform and then it is their responsibility. Their choice.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

When You Are Not 100% Sure

- Develop a relationship with a someone that has the expertise to assist your efforts.
- Do not guess, hope or assume you are right.
- Learn from them, develop your own expertise.
- Avoid those that are just out to sell something.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Grounding & Bonding

- Grounding, (Earthing) is the foundation of the electrical system.
- Bonding is the “rebar” that holds the foundation together.
- The electrical system is not safe or sustainable unless the grounding & bonding are completed to the highest possible standard.
- Anything built upon a flawed foundation will never be proper or sustainable regardless of the effort with which it is built.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What's Next

- Understand what makes up soil resistivity.
- Know the variables in grounding conditions.
- Understand the different types of grounds.
- Understanding ground testing.
- Ground Augmentation—What works & or will not.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What's Next

- Learn about high performance bonding.
- Ground Loops – Learn how to avoid them.
- Why grounding & bonding are critical for SPD.
- SPD – What you need to know about SPD.
- SPD – Your role in making sure they work.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

But First

- Lets look at some examples of very poor workmanship and talk about the down side of these examples.
- Who do you blame for these?
- Who is responsible?
- Do you want your equipment connected to these grounds or ground bonds?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



- Two Wires under the same lug.
- Improper lug for the wire size.
- Screwed, not bolted.
- Connected to painted steel.
- No conductive grease.
- Steel not continuous or contiguous.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The lightning arrestors for this phone system are not bonded to a path to ground. This is a life safety issue as well as a formula for equipment damage.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

This Met Code When Installed!



- As a result it meets code today!
- But, is it satisfactory?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Want Your Name on This Job?





2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



This is one of many electrical systems in a HUGE resort's in central FL.
MS1's Bond is shown to the left, MS2's Bond is show above...(missing).
THIS PASSED INSPECTION



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



This phone system is so unreliable the company that is the owner's telecom contractor kept a box full of replacement cards as they failed all the time. Annual cost? Over \$100,000.00 and they thought that is normal. After the FIX, no damage in years. State of Florida agency site!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



The above photo's are from a State of Florida site (500,000 Square Foot Building) Computer Room – where all the file servers and main blade server banks are. Call it computers city..... The computer person he wanted to make sure the critical equipment was grounded properly so he had additional ground rods, ground bonding bars added.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Wonder Who Approved This?



Want your new HD, Smart, Flat Screen TV on this ground? How about the fire alarm in a Children's hospital?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Tape Holding the Ground Bonding?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

This Was At a 9-1-1 Center



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Very Expensive Copper Theft!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Nice bonding job..... to What?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Bonding to Building Steel

The code allows it, but in a lightning prone environment this is trouble!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What is wrong here?




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What should be done here?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

A proper Ground Test Well



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning vs. Concrete Footer



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Path in but not a good one out!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The Reason for the Damage

Burn scar on shattered concrete is evidence that lightning found a vertical reinforcing rod (center), which likely acted as an efficient Ufer ground, offering lower resistance than that of the installed grounding/lightning protection system.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Testing Ground Systems Performance

- NEC 250 Grounding Performance Requirements.
None!
- NFPA 780 Grounding Performance Requirements.
None!
- UL96A Grounding Performance Requirements.
None!
- IEEE Grounding Recommendations.
5-Ohms or less.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

5 – Ohm Grounding

- Should be the requirement for the ground rod system of every electrical system.
- Ufer grounding & bonding is in addition to the 5-Ohm ground rod system.
- The maximum resistance of a lightning protection system ground rod should be 5-Ohms.
- All this added together, properly bonded will assure the odds of damage to the facility is VERY slim.
- Add to this a properly designed and installed surge protection system and the probability of any damage comes close to “0”.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Soil Resistivity


To determine the resistivity of the soil, the Wenner four-point measurement method (my choice of the two options), it corresponds to IEEE Std. 81.

The Wenner 4-point measurement test employs 4 test probes, spaced apart from each other at equal distances (the distance is critical).



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Note the distance between probes!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Long-form Wenner Formula

Four Point Soil Resistivity Test layout. Wenner Method:



ρ_E = measured apparent soil resistivity (Ωm)

a = electrode spacing (m)

b = depth of the electrodes (m)

R_W = Wenner resistance measured as "V/I" in Figure (Ω) If b is small compared to a , as is the case of probes penetrating the ground only for a short distance.

$$\rho_E = \frac{4 \cdot \pi \cdot a \cdot R_W}{1 + \frac{2 \cdot a}{\sqrt{a^2 + 4 \cdot b^2}} - \frac{a}{\sqrt{a^2 + b^2}}}$$



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Simplified Wenner Method




Fig. 1: Four-terminal method of measuring earth resistivity

Dr. Frank Wenner of the U.S. Bureau of Standards (now NIST) developed the theory behind this test in 1915 (see reference pg. 76). He showed that, if the electrode depth (B) is kept small compared to the distance between the electrodes (A)¹, the following formula applies:


$$\rho = 2\pi AR$$

where ρ is the average soil resistivity to depth A in ohm-cm, π is the constant 3.1416, A is the distance between the electrodes in cm, and R is the Megger earth tester reading in ohms.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Temperature & Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The “Depth” Require to Reach:

SOIL RESISTIVITY	LENGTH FOR A 5-Ohm GROUND	LENGTH FOR A 10-Ohm GROUND
50 Ω-M	33 Feet	9.8 Feet
70 Ω-M	52.5 Feet	20 Feet
100 Ω-M	85 Feet	33 Feet
150 Ω-M	145 Feet	59 Feet
200 Ω-M	207 Feet	85 Feet
300 Ω-M	344 Feet	144 Feet
500 Ω-M	636 Feet	276 Feet
1000 Ω-M	1444 Feet	636 Feet



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The Factors That Impact Soil Resistivity

- Electrolytes which consist of Moisture, Minerals and dissolved salts.
- Regardless of electrolyte content dry soil has high resistivity (Florida “Sugar Sand”)
- The highest resistance “normal” soil conditions are: Gravel, Sand & Stones with little or no clay and/or loam.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Resistivity of Soil Types

Chart is Influenced by Temperature and Moisture

Soil	Resistivity (approx.), n-cm		
	Min.	Average	Max.
Ashes, cinders, brine.waste	590	2,370	7,000
Clay, shale, gumbo or loam	340	4,060	16,300
Same, with varying proportions of sand & gravel	1,020	15,800	135,000
Gravel, sand, stones with little clay or loam	59,000	94,000	458,000



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Temperature and Resistivity*

<u>Temperature</u>		<u>Resistivity</u>
<u>C</u>	<u>F</u>	<u>Ohm-cm</u>
20	68	7200
10	50	9900
0	32 (water)	13,800
0	32 (Ice)	30,000
-5	23 (Ice)	79,000
-15	14 (Ice)	330,000

- *As temperature varies throughout the seasons therefore soil resistivity will also vary with the moisture content and the temperature. This is one of the reasons deep earth grounding is preferred in areas where the “frost line” is deep. A 10’ ground rod in some areas does not provide a ground in all seasons.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Resistivity of Various Waters

Classified Water	$\Omega - m$
Pure Water	200,000
Distilled Water	50,000
Rain Water	200
Tap Water	70
Well Water	20~70
Mixture of River & Sea Water	2
Sea Water (Inshore)	0.3
Sea Water (Ocean 3%)	0.2~0.25
Sea Water (Ocean 5%)	0.15


Table 9 : Resistivity of Water(Approx.Value)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Depth of Rod


- Depth has significant effect



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Diameter of Rod

Diameter has little effect



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Ground Rod Resistance & Rod Size

Increasing the diameter of the ground rod does little to reduce the resistance to earth.

Doubling the diameter reduces the resistance by less than 10%.

The only logical reason for a larger rod is the soil conditions (aka: Conditions require a $\frac{3}{4}$ " or larger ground rod so the rod can be installed. It is not unusual to have to "drill rock" or other hard earth structure.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Why These Factors Are Important

- $I = E/R$
- Current is what causes the damage
- The most current will flow when R is minimal (in the ground system)
- So you can have all the voltage you can imagine and if the “R” of the intended path is close to “0” you have “0” damage inside.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Annual Ground Testing

- The technician that completes ground testing must have been trained by the factory or their approved training representative.
- The technician **MUST** be certified to complete the testing.
- It is recommended the technician have a minimum of 5-years experience.
- A detailed written report with photo's must be provided.
- Anything less is **NOT** reliable.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Which Ground Tester(s) will meet your needs & testing requirements?

- Ground testers come in two versions. Stake type testers & clamp-on ground testers.
- Before you decide which style will meet your needs, understand the benefits & limitations of each tool.
- Suggested sites: Megger.com and AEMC.com



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

After training on both types this list is logical.

The Fall-of-Potential Checklist

- Identify and locate any and all conductive elements (wires, pipes, cables, metal fences, tree roots, etc.) or any condition or conductive element in the soil that would impact the test results.
- To insure accuracy of a “stake type” fall of potential test it is necessary to verify the test results. This is done by a completion of two additional tests that are at: 90°, 180° or at 270° from the initial test. This confirms there is no conductive elements.
- Do you have access to enough area or real estate to allow completion of two additional tests? If you cannot do both you don't have a reliable initial test.
- Verify the soil is un-disturbed and virgin soil, no fill has been added.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Fall-of-Potential Tester Checklist

- If necessary use ground penetrating radar to be sure the soil in the area can be used for testing.
- Verify the moisture content of the soil does not exceed the worst case lack of seasonal moisture.
- Test and record; the soil temperature, moisture content, PH, salt content.
- Confirm if any ground enhancement material was used when the grounding was installed. If anything other than Bentonite or conductive concrete the testing may (will) not be accurate.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Ground Rod Fall of Potential Testing & Concentric Shells of Earth



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV




FIGURE 11.17
Effective resistance areas (cylinders of earth) (a) overlapping and (b) not overlapping.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

“Adding a second rod does not provide total resistance of half that of a single rod, unless the two are several rod lengths apart.”

IEEE Green Book



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Fall-of-Potential Ground Testing




Fig. 10: Principle of an earth resistance test



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Distance in feet to the Auxiliary Electrodes Using the 62% Method**

<u>Depth Driven</u>	<u>Distance to "Y"</u>	<u>Distance to "Z"</u>
6	45	72
8	50	80
10	55	88
12	60	96
18	71	115
20	74	120
30	86	140


** The above is for "average" conductive soil with a 5% moisture content. The distances will triple if the soil has 10% moisture content and increase 12 times if the soil has 20% moisture content.



CONFERENCE & EXHIBITION

SEPTEMBER 24-28 | LAS VEGAS, NV

Band of Error Fall-of-Potential



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lowering Ground Resistance

- Add More Rods
- Deep Driven Rods
 - Threaded Couplings
 - Compression Couplings
 - Exothermic Ground Rod Splice



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Grounding vs. Bonding

- Art. 250's requirements for grounding and bonding, which begin in 250.4, can be broken down into two groups: Grounded & Ungrounded systems.
- Grounded systems [250.4(A)] Grounding (Earthing) metal parts of electrical equipment in or on structures.
- Ungrounded systems don't have a winding grounded at the supply transformer. That is the only difference.
- Grounded or Ungrounded you **MUST** bond enclosures and equipment together.
- The difference in Ungrounded systems you are bonding the equipment together, rather than each other and the source. (The bond to the source is missing.)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Grounding & Bonding for Lightning

- Lightning strikes most often occur to outside wiring.
- Grounding & bonding the electrical system will assist the flow of lightning into the earth.
- The electrical system is a calibrated spark gap.
- Over voltages will arc to a lower potential.
- If the lower potential is capable of handling the current that will develop you divert what would otherwise be trouble.
- Low resistance & impedance ground paths facilitate that to happen.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Bonding to the Highest Level

- Bonding should be designed and installed to a level that will provide a very low impedance path to the facilities electrical system earth ground.
- Bonding must be robust, use stranded cables and have a “flow” to the earth ground.
- Bonding must not have hard bends.
- Bonding must be installed with the capability to channel the flow of lightning energy to earth ground with no equipment damage.
- Bonding must be logical.... It is not just a green wire connected to something.
- NO cross contamination.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Bonding Installation

- Electrical service entrance ground bonds should be to a common bonding bar that is both robust and provides a low impedance path to earth ground.
- All bonds should be exothermic welds or double lugs and made using conductive grease and robust hardware. (lock washers, double nuts, etc.)
- This bonding bar should be the common point of all bonds: Neutral, plumbing, water, gas pipe, lighting protection, Ufer, building steel, all metallic elements of the electrical panels, conduit, etc.
- Allow for the flow of lightning energy imposed on any and all elements of the electrical system.
- Bonding must be “serviced”, verified, checked, etc.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Improve Bonding Installations


- Bring footer rebar out of the footer in an 18” radius bend to 1’ above the floor adjacent to the service entrance.
- A minimum of two 20’ sections of rebar should be 1’ apart. (more is better)
- The Ufer bonds to be exothermic welds with 4/0 bare copper.
- Connect the 4/0 copper bonding bar with high compression double lugs (or exothermic welds).
- Connect the X/O bond to the bonding bar.
- Connect all outside services (CATV & Telecom) bonds with home runs to the bonding bar.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SPD (TVSS) Placement

Use Surge Suppressors in a "system" approach.




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Series Installed Surge Suppressors for critical circuits!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Only N-G Bond is at Service (or separately-derived system)



Source: Dranetz Field Handbook



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Internal Causes of PQ Problems

- Poor electrical system design and layout
- Lack of or inadequate electrical system maintenance
- Shared mixed load distribution panels
- Too many outlets per circuit
- Mixed load use on circuits
- Inadequate and shared neutrals
- Poor, inadequate and shared grounding
- Intermittent connections
- Standard equipment and wiring (inadequate conductors, IG, etc.)
- etc.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning Protection Systems

- The codes and standards for lightning protection systems allow building steel to be used as the “down conductor”.
- Simply put the steel framework of a building becomes the conductor for lightning.
- What happens to the metal conduit that is in contact with the building steel?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Improper Bonding

- The building's metal studs are a ground reference path for the metal equipment cabinet of the system to attach to them.
- The case ground wire connects the control board to the ground reference of the metal studs.
- The electrical ground and the metal studs become a ground loop.
- Lightning strikes the building or nearby the building and electrical energy flows between the grounds.
- ZAAAAAP! System(s) down!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SPD Quality = Performance



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

AC Power Surge Protection Devices

- SPD are classified by UL based upon how they are installed
- Type “1” – Hardwired ahead of the main means of disconnect.
- Type “2” – Hardwired after the main means of disconnect.
- Type “3” – Cord connected or direct plug in devices.
- Type “4” – Component Assemblies – One or more components that are listed as part of Type 5.
- Type “5” – Individual components such as MOVs.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

What To Use Where (ratings in kA per mode)

- Service Entrance – 100kA to 300kA.
- Primary Distribution – 100kA to 200kA.
- Distribution “outside loads” – 100kA to 200kA.
- Distribution panels – 50kA to 100kA.
- Sub Panels – 40kA to 50kA.
- Outside Loads – 40kA to 50kA series device.
- Critical Loads – 50kA series device.
- Point of use – Cord connected 10-20kA.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Rating SPD – What is Important

- NEMA LS-1 1992 Testing.
- Rated kA per mode rather than by phase.
- SPD Noise Filters are rated in dB.
- SPD manufacturer reputation for SPD.
- Expert application support.
- SPD manufacturers field support.
- SPD manufacturers warranty policy.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

The SPD Layered or System Installation

- Ahead of the main means of disconnect.
- Automatic transfer switch both line & load.
- To protect the main
- To protect all distribution panels.
- To protect critical circuits.
- To protect circuits that exit the facility.
- To protect elevators.
- To protect point of use devices.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Wiring Practice

- Surge Suppressors should be connected to a full size grounding conductor
- By “full size” I mean equal to the phase size



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Minimal Wire Length Is Critical



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Wire Length is DELAY!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

But NOT a local ground rod!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Code Violation & more!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

AC Power SPD & Facility Protection

- Proper “facility” protection is much more than the installation AC power SPD.
- Coordinate with other service providers: CATV, Telecom, etc.
- Be sure they have connected properly to the ground bonding system.
- Be sure they have also protected their services.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Installation Conditions

- Geographic Considerations.
- Building Construction.
- System Topology.
- Power distribution system configuration.
- Control cabinet or equipment location.
- Interface considerations.
- Customer specific requirements.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Poor Location Example

Proper grounding can be done.

Mt. Washington, NH



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Mt. Washington, NH

Two 600 feet deep copper rods placed in 8 inch diameter well casings

Backfill with bentonite grout

Interconnect with 500 kcmil copper cable


Achieved 6 ohm resistance



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Site Layout

- 500 kcmil ring grounds (B)
- 2-600 ft. deep vertical electrodes (A)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Deep Electrodes

Through a mountain



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Cost-effective

Before:

3-4 major events in 2 years (lightning)

\$120,000 average equipment damage per year
plus lost ad revenue (station downtime)

After:

No damages or disruptions in >10 years since
improved grounding

Source: R. Cushman, Chief Engineer, WMTW-TV



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

System Installation Options

- Geographic conditions should be considered when connectivity of devices within a system is determined.
- Distance of the connection must be considered.
- Device location (inside or outside) the facility will impact the connectivity option considerations.
- System expansion plans will impact the initial system installation.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

WRZN

Multiple things to learn



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Where to Place Electrode?

A/C makes perfect
moisture drip



2017 BICSI
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

WRZN

Original 280 Ohms



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

WRZN

After new grounding
3.4 Ohms



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Telephone Service

Lightning does not
travel up!

ground bar was there
all the time.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Mutual Induction

Neat but induction
will worsen situation



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning is Frequently on Telephone System

Telephone and cable TV mixed on common ground bar.

Lightning will be transferred to cable TV, then electric system



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Fire & Security Alarms

- Plan the layout – consider wire run options.
- Networks are nice, however long wire runs increase exposure to lightning damage.
- Avoid problems – use shielded wire.
- Understand how to bond the shield.
- Avoid ground loops – know your connection.
- Isolate if you are not 100% sure.
- Select the right technology.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Guidelines

Circuitry

Voltage Drop

Full Size Conductors

General Principals



2017 BICSI *Fall* Source: Branetz Field Handbook
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Avoiding Ground Loops

There should be **ONE** central point connecting the interior wiring to the **ONE** exterior grounding electrode system



2017 BICSI *Fall* Source: Dranetz Field Handbook
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Avoid Ground Loops




Never use the earth as a ground path



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Only N-G Bond is at Service (or separately-derived system)




• Source: Dranetz Field Handbook



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Example of “star” grounding



Source: EC&M Guide to Quality Power



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Avoid Conduit as a Ground Path

Can you imagine a
joint every 10 feet?




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Full Size Equipment Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Will That Conductor “Fuse”?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


General Wiring Practice

- **Sensitive loads should be separated:**
 - **Separate branch circuits**
 - **Separate panelboards**
 - **Separate feeders**
 - **Separate transformers**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Typical Wiring Method




source: IEEE
Emerald Book



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Slightly Better Wiring Method




source: IEEE
Emerald Book



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Much Better Wiring Method




source: IEEE
Emerald Book



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Optimal Wiring Method



source: IEEE
Emerald Book



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Wiring Practice


- Limit the number of outlets per circuit:
- 3-6 per 20 amp. branch circuit (maximum):
- Prevent interaction among loads
- Limit voltage drop



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Wiring Practice

- Use Surge Suppressors, connected to a full size grounding conductor
- - at the service
- - at the panelboard
- - at the load



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Wiring Practice

Surge Suppressors:

**Must be well-grounded
to work**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

General Wiring Practice

Surge Suppressors Should Have:

- All-mode protection: ϕ - ϕ , ϕ -G, ϕ -N, N-G
- Listed to UL 1449, Version 3
- High Joule (W•Sec) rating
- Have filtering, fuses, indication
- Must be well-grounded to work



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Caveat

MOV's can degrade with use!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Suncoast Schools FCU



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SunCoast FCU



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Data Center Inside




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning Hit Service Drop



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SunCoast Credit Union's Data Center 480Y/400-Amp Meter Base Disconnect



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

7 Levels of SPD's



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning vs. The Meter Base

- The meter base took the brunt of the lightning damage.
- The meter base housing was “bonded” to the ground system.
- The impedance of the path to the switchgear higher than the path to the ground rod system.
- Nothing inside the data center was damaged.
- The most robust was a SPD was rated at 120kA per mode.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Lightning vs. The Meter Base

- The lightning energy imposed on the electrical service went to earth ground on the conductor that bonded the meter base and other metal cases of the electrical system to the ground rod system.
- The ground resistance of the service: 4.3 Ohms (Fall-of-Potential) tested.
- The only damage was to the “outside” elements of the electrical service. (Meter base, gutter work, pole, transformer, utility wires, etc.)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

SPD's Need Good Ground

Without a good, low impedance ground to discharge to SPD's don't work.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Suncoast's Data Center

No downtime


No equipment damage

Cost around \$40,000




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Think of a “current divider”



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Desired Grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Example of Current Divider

Macomb County, MI 9-1-1



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Note Tower in Rear



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Gas and Water Services Bonded



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Labeled So No One Removes



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Conductor Welded to Base, Not Tower Leg



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Coax Braid Bonded on Vertical Run



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Then to Strap at Bulkhead




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Inside Radio Room



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Rolling Ball



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Costs

- **Cost of materials is CHEAP compared to labor, equipment, downtime**
- **Cost for all PQ improvements:**
- **Adds about 1 to 1-1/2% to the overall cost of construction, but....**

- **Never have to revisit infrastructure for foreseeable future**




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

One Summer Street, Boston




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Each Rack Tied to Overhead Bus



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Rows of Racks to Ground Bus



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Separate Conduits to Master Ground Bus



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Master Ground Bus (MGB)

- Note that all conduits are labelled.
- MGB located at lowest point in building.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Never Rely on Conduit for Ground

- Always use a full-sized separate copper ground conductor




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Start With Ring Ground



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Network of Air Terminals



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Heavy Duty Down Conductors

Not steel
framing




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Do Not Use Building Steel




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Surge Suppression



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Overall Result



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

System Grounding

There should be **ONE and ONLY ONE** point connecting the neutral to the exterior grounding electrode system





Figure 6. Facility Grounding System



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

No “independent” grounds



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Interior Review

- **Separate circuits, panels for sensitive loads**
- **Limit receptacles to 3-6 per circuit**
- **Limit voltage drop to 3% or less (Code) 2% recommended.**

wire gage, circuit length



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Surge Suppressors


Keep leads as short as possible



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Surge Suppressors (SPD's)

- at the service
- at the panel board
- at the load




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

TVSS Placement

Use Surge Suppressors in 3 places

- At the service
- At feeder level
- At branch level



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

At the Service Level

Type 1 devices

150 kA per mode minimum suggested



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

At the Feeder Level

Type 2 devices

75 kA per mode minimum suggested



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

At the Device Level

Type 3 devices

25 kA per mode min.


50 kA if critical load



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Use Grounding Conductor

Always use a full size copper equipment grounding conductor
– do not rely on conduit



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Trap Harmonics



Shielded isolation transformer
sometimes helps Isolate harmonics



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

To Handle Harmonics

Use a 200% rated neutral or separate neutrals per phase




2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

N-G Bonds


Interior:

- Check neutral – ground voltage
 - could mean harmonics
- Check for ground current
 - illegal N-G bonds



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Use Only Listed Connectors



- Automotive hose clamps
- Water tube conductor



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Limit Voltage Drop

- NEC does not mandate voltage drop
- Limit Vdrop to 3% maximum in branch circuits, less if practical
- It's the law in CA, NY, IL, maybe other states



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Environment Considerations



- Automotive hose clamps
- Undersize conductors
- Rust
- Different metals



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Low Resistance is Vital



- Under 5 ohms
- Spacing 2X length
- Below frost line



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Choice of rod types

Pick the right rod for the
soil conditions



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Bentonite

- Bentonite is a Ground Improvement Material.
- Bentonite is not a Ground Enhancement Material. (There is a difference.)
- GIM is:
 - Naturally Inert.
 - Compactable & soil compacting.
 - Have low and stable resistivity.
 - Able to maintain low resistance with minimal fluctuations.
 - Does not leach with time.
 - Economically viable.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Backfill

- Bentonite is the recommended backfill
- Conductive concrete second

Be wary of anything
containing graphite



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Augured Hole with Rod & Bentonite

- A hole is augured into the soil.
- The hole is filled with Bentonite.
- A ground rod is installed into the center of the augured hole and the conductor is exothermically welded to the rod.
- Water is added, the Bentonite swells and fills all the voids.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


Benefits of Bentonite

- The formation of an electrolyte when Bentonite is ionized by water & this layer around the grounding electrode serves as a pathway for dispersion of lightning charges.
- Increased current dispersion of lightning when compared to installations lacking Bentonite.
- Bentonite is the only Ground Improvement Material approved and recommended by the Copper Industry. (re: copper.org)



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Chemical Ground Rods



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV


What is a Chemical Ground Rod?

- Simple version: Salt in a Copper pipe with holes drilled into it that is installed in the earth where the moisture will cause the salt to leach into the soil.
- The truth, it is a very viable grounding solution “IF” you understand what it is, what is needed to maintain it (AKA Replace it in time).
- The bottom line is what works in one environment may or may not work in another.
- Use what is most cost effective, sustainable and reasonable in cost for your application.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

A chemical ground rod in action a
Copper pipe full of salt will last how long?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Chemical Electrodes

Salt-filled pipe after 7 years



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Ground Enhancement Material

- GEM is marketed as the best way to lower the resistance in difficult grounding conditions.
- GEM is a product that is a “waste” or by product of a manufacturing process. GEM does not subject to a quality control process or procedure that would insure it is not corrosive.
- Depending on “luck” and not knowing if you are installing a highly corrosive product that will be all around a soft metal (copper) is not a wise decision.
- If you wish to ignore the issue with corrosion, just use the “cheap version” of GEM, Rock Salt or fertilizer of some type.
- Carbon “enhanced” or based products are know to be corrosive and not recommended.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Galvanized Rod After 7 Years



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Galvanized Rod


$\frac{3}{4}$ inch to pencil-thin



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV



Use bolt-in Circuit Breakers

Twist-lock plugs/receptacles



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Harmonic rated panels and transformers



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

First Step


Get the wiring and grounding right

This may solve the problem at minimum cost!



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Buy What I Sell



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Grounding System Must be Checked

Check resistance of grounding electrode system annually (or more often as conditions dictate).



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Is Ufer Actually Grounded?


Bonded to rebar?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Building Steel Was Not Grounded

2 transformers were grounded to building steel, but steel was not bonded to ground electrode




Sumter County 911



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Review

- Interior:
- Bolt-in circuit breakers
- Twist-lock plugs/receptacles



2017 BICSI
CONFERENCE
SEPTEMBER 24-28 | LAS VEGAS, NV

Does Lightning Flow Up?

Telephone grounding



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Are connections proper?

Look for paint or other insulation



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Do Not Mix Load Types



PANELBOARD/PANNEAU/TABLERO

SOURCE		V	LOAD / CHARGE / CARGA		DATE:
CIR	LOAD / CHARGE / CARGA		CIR	LOAD / CHARGE / CARGA	
1	Elevator main		2	Lobby A.H.U	
3	disconnect		3		
5	Hyd. motor		5		
7	Lobby A/C		8	Surge	
9	condensate unit		10	Protection	
11	out Rack		12	unit	
13	Parking lot		14	Hot water	
15	Light poles		16	Heater	
17	Parking lot		18	spare	
19	Light poles		20	South Stair way LTS	
21	outside front GFI		22	SPare	
23	N+S GFI		24	North Stairway LTS + Emergency LTS	
25	GFI switch		26	Elevator Cab LTS	
27	PHOTO cell		28	Fresh Air make up Fan	
29	Entry Lobby GFI		30	Time clock	
31	Fire Alarm Booster Pnl.		32	Elevator PIT QFI	
33	Fire Alarm Pnl.		34	Elevator PIT LSTS	
35			36		
37			38		
39			40		
41			42		



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
 SEPTEMBER 24-28 | LAS VEGAS, NV

Separate Circuits

Sensitive loads should be separated:

- **Separate branch circuits**
- **Separate ground conductors**
- **Separate panelboards**
- **Separate feeders**
- **Separate transformers**
- **BUT everything must be bonded together**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

With Many Projects There Are 6 Phases

1. Enthusiasm!
2. Disillusionment!
3. Panic!
4. Search for the Guilty!
5. Punishment of the innocent!
6. Praise for the non-participants.

Where to you want to be on the above list at the end of the day?



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Take-aways

1. Exceed the Code, but don't violate the Code!
(Code minimum is one step above "illegal")
2. You don't get what you expect,
you only get what you inspect.
Contractors do not get final payment until inspection



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Take-aways

3. Have a written plan and procedures.

Insist contractors follow it.

**4. Get the grounding and bonding right before anything else.
Most lightning and transient problems can be cured at
minimal cost.**



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Tips

This stuff isn't taught in school.

“A man's got to know his limitations.”

- Clint Eastwood as Dirty Harry


Call in a professional when there is doubt.



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV

Free Educational Seminars

- www.copper.org/electricalseminars
- Case Histories
- Recommendations
- Bibliography
- CD-ROMs, DVDs



Thus, while not having a strict basis measurement, terms like "poor power quality" generally mean there is efficient deviation from norms in the power supply to cause equipment misoperation or premature failure. "Good power quality," conversely, means there is a low level of such deviations mis-operations. Because the sensitivity to such violations varies from one piece of equipment to another, what may be considered poor power quality for one device may be perfectly acceptable power quality for another. Poor power quality affects the reliable operation of computers and computer-based equipment, which are now so ubiquitous. Often more important than the physical effect on the equipment is the loss of productivity.

**APP
DAT**

COPPER

**A Prim
Power**

201 Madison Avenue, New York, NY 10017
Tel: (212) 251-7200 Fax: (212) 251-7224

Copper Development Association Inc.
<http://www.copper.org>

Power Quality Issues and Recommendations

	Old Practice or Code Minimum	Helpful Procedures or Current Recommended Practice
Receptacle outlets per 20 amp circuit	13 maximum	3 1/2 maximum
Neutrals	Shared neutral, or even doublet neutral (on 3-phase systems)	Use double-size neutral or larger on 3-phase systems

COPPER DEVELOPMENT ASSOCIATION

POWER QUALITY

V 3.0

Video segments and text include segments that discuss:

- Equipment grounding and bonding
- Harmonics
- Transients and lightning
- Power conditioning and surge protection
- Robust wiring for power quality considerations
- Case histories



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
 SEPTEMBER 24-28 | LAS VEGAS, NV

Thank You!

David Brender

Copper Development Association Inc

(212) 251-7206

(561) 894-8901

Email: david.brender@copperalliance.us

www.copper.org

www.copper.org/electricalseminars



2017 BICSI *Fall*
CONFERENCE & EXHIBITION
SEPTEMBER 24-28 | LAS VEGAS, NV